




rotate lens counterclockwise for 8x view



rotate lens clockwise for 3x view



Rotate front lens for continuous 3-8x Zoom



Advanced recording capabilities



Quick-release Picatinny mount



Optional Clip-On attachment

Thermal Imager T15™ with Real Optical 3-8x Zoom

T15 mini-thermal imager offers unique Optical Zoom from 3 to 8x in a tiny package. The device offers the following features:

- On-board image enhancement
- Shutter with automatic NUC capability
- Video and Photo on-board recording
- USB port with power input and software updates
- Auto power-save
- Multiple display views: white hot / black hot / NV green / color
- Flexible mounting options: tripod mount / Weaver mount and more...
- Optional: 2x optical lens adapter
- Clip-On Attachment for interfacing with optical scopes

9Hz unit is ideal for surveillance and is export ready. Device can be used in variety of search operations, firefighting and detection and other commercial applications.

	T15-C	T15
Size	4.1" x 2.7" x 1.7" (105 x 70 x 44mm)	4.5" x 2.7" x 2.5" (114 x 79 x 70mm)
Weight w/o battery	225g	310g w/ mount
Zoom	3-8x Continuous optical zoom with auto focus adjustment	
Field-of-View	from 18.7° to 7°	
Minimum Focus Distance	2 meters	
Range Performance	Human Detection Range: 162m @ 3x – 436m @8x Human Recognition Range: 81m @ 3x - 218m @ 8x Human Identification Range: 40m @ 3x - 109m @ 8x	
Focus	Focus free	
Special Range	8-14 micron	
Power	2 CR123, 3V – 8+ hours of operation	
Resolution	160x120 pixels FLIR Lepton 3	
Display	1.5" OLED	
Operating Temperature	-10° to +45° C	
Frame Rate/Shutter	9Hz with Shutter	
Accessories	Optional 2x afocal adapter; Optional Clip-On adapter	

